

## Wall mounted receptacle

Part no. 1825



- screw terminals
- external fixing
- one cable entry at top and one blind cable entry (can be cut out) at the rear side

## Technical specifications

|                       |                 |
|-----------------------|-----------------|
| Ampere                | 16 A            |
| Poles                 | 2 p             |
| Voltage               | 20-25 V         |
| Hertz                 | 50-60 Hz        |
| Connection technology | Screw terminals |
| Contact               | standard        |
| Protection type       | IP 44           |
| Weight                | 189 g           |

## Drawing

| Drawing<br>1 MB 294  | Amp.<br>Poles | 16  |     | 32  |     |
|--|---------------|-----|-----|-----|-----|
|  |               | 2   | 3   | 2   | 3   |
| Dim. in mm   | a             | 96  | 96  | 96  | 96  |
|  | b             | 73  | 73  | 73  | 73  |
|  | c             | 90  | 90  | 90  | 90  |
|  | d             | 53  | 53  | 53  | 53  |
|  | d1            | 52  | 52  | 52  | 52  |
|  | d2            | 2   | 2   | 2   | 2   |
|  | e             | 62  | 62  | 62  | 62  |
|  | f             | 5.3 | 5.3 | 5.3 | 5.3 |
|  | g             | 8   | 8   | 8   | 8   |
|  | h             | 129 | 129 | 129 | 129 |
| Terminal for cond. cross<br>section (mm <sup>2</sup> ) min.-max. |               | 4   | 4   | 4   | 4   |
|  |               | -10 | -10 | -10 | -10 |