

## Connector ProTOP

Part no. 201




- screw terminals
- cable gland and sealing
- strain relief and protection against kinking
- enclosure with thread lock and safety slide

## Technical specifications

|                       |                 |
|-----------------------|-----------------|
| Ampere                | 16 A            |
| Poles                 | 3 p             |
| Voltage               | 50-500 V        |
| Clock position        | 10 h            |
| Hertz                 | 100-300 Hz      |
| Connection technology | Screw terminals |
| Contact               | standard        |
| Protection type       | IP 44           |
| Weight                | 175 g           |

## Drawing



| Drawing<br>3 MB 60                   | Amp.<br>Poles | 16   |      |      | 32  |     |     |
|--------------------------------------|---------------|------|------|------|-----|-----|-----|
|                                      |               | 3    | 4    | 5    | 3   | 4   | 5   |
| Dim. in mm                           | a             | 160  | 174  | 172  | 214 | 214 | 210 |
|                                      | b             | 57   | 61   | 69   | 75  | 75  | 80  |
|                                      | h             | 83   | 92   | 98   | 100 | 100 | 108 |
|                                      | y             | 16   | 16   | 16   | 22  | 22  | 22  |
| Terminal for cond. cross             |               | 1    | 1    | 1    | 2.5 | 2.5 | 2.5 |
| section (mm <sup>2</sup> ) min.-max. |               | -2.5 | -2.5 | -2.5 | -6  | -6  | -6  |