

Connector PowerTOP®

Part no. 3898




- screw terminals
- with highly heat resistant contact carrier
- cable gland and external cable grip

Technical specifications

| Ampere | 32 A |
|---------------------------|---------------------------------------|
| Poles | 4 p |
| Voltage | 500 V |
| Clock position | 7 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | highly heat resistant contact carrier |
| Protection type | IP 67 |
| Weight | 379 g |
| Declaration of Conformity | DE,VDE |

Drawing



| Drawing | Amp. | | 16 | | | 32 | |
|--------------------------|-------|--------------|--------------|------|------|---------------|------|
| 3 MB 48/3 | Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | а | 171 | 182 | 194 | 217 | 217 | 229 |
| | b | 78 | 85 | 96 | 103 | 103 | 110 |
| | h | 79 | 88 | 95 | 99 | 99 | 105 |
| | у | 19 | 19 | 22 | 24.5 | 24.5 | 28.5 |
| | | | | | | | |
| Terminal for cond. cross | | 1 | 1 | 1 | 2.5 | 2.5 | 2.5 |
| section (mm²) minmax. | | — 2.5 | — 2.5 | —2.5 | 6 | 6 | 6 |