

## Wall mounted receptacle with TwinCONTACT

Part no. 7146




- fused with circuit breaker
- K-characteristics

### Technical specifications

|                       |                 |
|-----------------------|-----------------|
| Ampere                | 32 A            |
| Poles                 | 4 p             |
| Voltage               | 400 V           |
| Clock position        | 6 h             |
| Hertz                 | 50-60 Hz        |
| Connection technology | Screw terminals |
| Contact               | standard        |
| Protection type       | IP 67           |
| Enclosure material    | Plastic         |
| Weight                | 1350 g          |

### Drawing



| Drawing<br>1 MB 378 | Amp.<br>Poles  | 16            |      |      | 32            |      |
|---------------------|--|---------------|------|------|---------------|------|
|                     |  | 3             | 4    | 5    | 4             | 5    |
| Dim. in mm          | a  | 225           | 225  | 225  | 225           | 225  |
|                     | b  | 118           | 118  | 118  | 118           | 118  |
|                     | c  | 144           | 146  | 147  | 152           | 153  |
|                     | d  | 208           | 208  | 208  | 208           | 208  |
|                     | e  | 101           | 101  | 101  | 101           | 101  |
|                     | f  | 6.3           | 6.3  | 6.3  | 6.3           | 6.3  |
|                     | g  | 8             | 8    | 8    | 8             | 8    |
|                     | h  | 252           | 255  | 259  | 268           | 274  |
|                     | M  | 1x25 and 1x32 |      |      | 1x25 and 1x32 |      |
|                     | M*   | 2x25          | 2x25 | 2x25 | 2x25          | 2x25 |
|                     | Max. cable diam. (mm)  | 25            | 25   | 25   | 25            | 25   |
|                     | Terminal for cond. cross section (mm <sup>2</sup> ) min-max. | 1.5           | 1.5  | 1.5  | 2.5           | 2.5  |
|                     |  | -4            | -4   | -4   | -10           | -10  |