

Wall mounted receptacle

Part no. 7169




- screw terminals
- X-CONTACT®
- fused with RCD (0.03 A)
- other leakage current ratings on request

Technical specifications

| | |
|---------------------------|-----------------|
| Ampere | 63 A |
| Poles | 4 p |
| Voltage | 400 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | X-CONTACT® |
| Protection type | IP 67 |
| Enclosure material | Plastic |
| Weight | 2600 g |
| Declaration of Conformity | CN,CQC |

Drawing



| Drawing | Amp. | 63 | |
|---|-------|------|------|
| 1 MB 619 | Poles | 4 | 5 |
| Dim. in mm | a | 264 | 264 |
| | b | 163 | 163 |
| | c | 191 | 191 |
| | d | 240 | 240 |
| | e | 140 | 140 |
| | f | 8.1 | 8.1 |
| | g | 8 | 8 |
| | h | 319 | 319 |
| | M | 40 | 40 |
| | M* | 2x40 | 2x40 |
| Max. cable diam. (mm) | | 27 | 27 |
| Terminal for cond. cross section (mm ²) min.-max. | | 6 | 6 |
| | | -25 | -25 |