

## Wall mounted receptacle

Part no. 767



- screw terminals
- internal fixing
- one cable entry at top and two blind cable entries (can be cut out) at bottom
- in 4 pole version enclosure base can be turned 180°

## Technical specifications

|                       |                       |
|-----------------------|-----------------------|
| Ampere                | 16 A                  |
| Poles                 | 3 p                   |
| Voltage               | Isolating transformer |
| Clock position        | 12 h                  |
| Connection technology | Screw terminals       |
| Contact               | standard              |
| Protection type       | IP 44                 |
| Weight                | 180 g                 |

## Drawing

| Drawing   | Amp.  | 16                        |     |     |
|---|-------|---------------------------|-----|-----|
| 1 MB 209  | Poles | 3                         | 4   | 5   |
| Dim. in mm  | a     | 87                        | 100 | 100 |
|   | b     | 64                        | 75  | 75  |
|   | c     | 99                        | 110 | 113 |
|   | d     | 40                        | -   | -   |
|   | d1    | -                         | 11  | 11  |
|   | e     | 50                        | 59  | 59  |
|   | f     | 4.5                       | 5   | 5   |
|   | g     | 4                         | 4   | 4   |
|   | h     | 115                       | 125 | 128 |
|   | M     | 20                        | 20  | 20  |
|   | M*    | M20 (blind) to be cut out |     |     |
| Max. cable diam. (mm)   |       | 15                        | 15  | 15  |
| Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. |       | 1.5                       | 1.5 | 1.5 |
|   |       | -4                        | -4  | -4  |