

## Connector StarTOP® with SafeCONTACT

Part no. 993




- screwless, with insulation displacing technique
- cable gland and sealing
- strain relief and protection against kinking
- enclosure with thread lock and safety slide

### Technical specifications

|                           |                         |
|---------------------------|-------------------------|
| Ampere                    | 16 A                    |
| Poles                     | 4 p                     |
| Voltage                   | 230 V                   |
| Clock position            | 9 h                     |
| Hertz                     | 50-60 Hz                |
| Connection technology     | Screwless - SafeCONTACT |
| Contact                   | standard                |
| Protection type           | IP 44                   |
| Weight                    | 228 g                   |
| Declaration of Conformity | DE, VDE, CN, CQC        |

### Drawing



| Drawing<br>3 MB 60                   | Amp.<br>Poles | 16   |      |      | 32  |     |     |
|--------------------------------------|---------------|------|------|------|-----|-----|-----|
|                                      |               | 3    | 4    | 5    | 3   | 4   | 5   |
| Dim. in mm                           | a             | 160  | 174  | 172  | 214 | 214 | 210 |
|                                      | b             | 57   | 61   | 69   | 75  | 75  | 80  |
|                                      | h             | 83   | 92   | 98   | 100 | 100 | 108 |
|                                      | y             | 16   | 16   | 16   | 22  | 22  | 22  |
| Terminal for cond. cross             |               | 1    | 1    | 1    | 2.5 | 2.5 | 2.5 |
| section (mm <sup>2</sup> ) min.-max. |               | -2.5 | -2.5 | -2.5 | -6  | -6  | -6  |