

## Wall mounted inlet

Part no. 2166



- screw terminals
- highly heat resistant contact carrier
- nickel plated contacts
- enclosure base with stamped recess for quick cutting out

## Technical specifications

|                           |   |
|---------------------------|---|
| Ampere                    | 16 A  |
| Poles                     | 7 p   |
| Voltage                   | 400 V   |
| Clock position            | 6 h   |
| Hertz                     | 50-60 Hz  |
| Connection technology     | Screw terminals   |
| Contact                   | nickel plated contacts, highly heat resistant contact carrier |
| Protection type           | IP 44   |
| Weight                    | 266 g   |
| Declaration of Conformity | CN,CQC  |

## Drawing

| Drawing  | Amp.         | 16                       | 32                         |
|--|--------------|--------------------------|----------------------------|
| <b>2 MB 147</b>  | <b>Poles</b> | <b>7</b>                 | <b>7</b>                   |
| Dim. in mm   | a            | 100                      | 128                        |
|  | b            | 75                       | 84                         |
|  | c            | 110                      | 135                        |
|  | d            | —                        | —                          |
|  | d1           | 10.5                     | 11                         |
|  | e            | 59                       | 68                         |
|  | f            | 5                        | 5.3                        |
|  | g            | 4                        | 4                          |
|  | h            | 135                      | 170                        |
|  | M            | 20                       | 32                         |
|  | M*           | 20 (blind) to be cut out | 2x25 (blind) to be cut out |
| Max. cable diam. (mm)  |              | 15                       | 18                         |
| Terminal for cond. cross section (mm <sup>2</sup> ) min-max. |              | 1                        | 2.5                        |
|  |              | -2.5                     | -4                         |