

Plug AM-TOP®

Part no. 297




- screw terminals

- single part body cable gland and sealing strain relief and protection against kinking

Technical specifications

| Ampere | 32 A |
|---------------------------|-----------------|
| Poles | 4 p |
| Voltage | 50-500 V |
| Clock position | 2 h |
| Hertz | 300-500 Hz |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP 67 |
| Weight | 320 g |
| Declaration of Conformity | DE,VDE, CN,CQC |

Drawing



| Drawing | Amp. | | 16 | | | 32 | |
|--------------------------|-------|------|--------------|------|------------|------------|-----|
| 2 MB 218 | Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 142 | 144 | 147 | 186 | 186 | 180 |
| | b | 70 | 78 | 87 | 94 | 94 | 101 |
| | n | 109 | 111 | 114 | 145 | 145 | 138 |
| | у | 14.5 | 16 | 16 | 22 | 22 | 22 |
| Terminal for cond. cross | | 1 | 1 | 1 | 2.5 | 2.5 | 2.5 |
| section (mm²) minmax. | | -2.5 | — 2.5 | —2.5 | <u></u> -6 | — 6 | 6 |