

**Connector PowerTOP®** 

Part no. 3860




- screw terminals
- with highly heat resistant contact carrier
- cable gland and external cable grip

## **Technical specifications**

Ampere	16 A
Poles	3 p
Voltage	230 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	highly heat resistant contact carrier
Protection type	IP 67
Weight	221 g
Declaration of Conformity	DE,VDE, CN,CQC

## Drawing



	16			32		
Poles	3	4	5	3	4	5
а	171	182	194	217	217	229
b	78	85	96	103	103	110
h	79	88	95	99	99	105
у	19	19	22	24.5	24.5	28.5
Terminal for cond. cross		1	1	2.5	2.5	2.5
section (mm <sup>2</sup> ) minmax.		-2.5	-2.5	-6	—6	—6
	a b h y d. cross	a 171 b 78 h 79 y 19 d. cross 1	a 171 182   b 78 85   h 79 88   y 19 19   d. cross 1 1	a 171 182 194   b 78 85 96   h 79 88 95   y 19 19 22   d. cross 1 1 1	a 171 182 194 217   b 78 85 96 103   h 79 88 95 99   y 19 19 22 24.5   d. cross 1 1 1 2.5	a 171 182 194 217 217   b 78 85 96 103 103   h 79 88 95 99 99   y 19 19 22 24.5 24.5   d. cross 1 1 1 2.5 2.5