

## Plug ProTOP

Part no. 658




- screw terminals
- cable gland and sealing
- strain relief and protection against kinking
- enclosure with thread lock and safety slide

## Technical specifications

|                       |                 |
|-----------------------|-----------------|
| Ampere                | 16 A            |
| Poles                 | 4 p             |
| Voltage               | 50-500 V        |
| Clock position        | 2 h             |
| Hertz                 | 300-500 Hz      |
| Connection technology | Screw terminals |
| Contact               | standard        |
| Protection type       | IP 44           |
| Weight                | 163 g           |

## Drawing



| Drawing<br>2 MB 214                  | Amp.<br>Poles | 16   |       |       | 32   |      |     |
|--------------------------------------|---------------|------|-------|-------|------|------|-----|
|                                      |               | 3    | 4     | 5     | 3    | 4    | 5   |
| Dim. in mm                           | a             | 148  | 160   | 160   | 197  | 197  | 197 |
|                                      | b             | 55   | 65.6  | 65.6  | 75   | 75   | 75  |
|                                      | h             | 61   | 72.5  | 72.5  | 80.5 | 80.5 | 85  |
|                                      | n             | 112  | 123.5 | 123.5 | 152  | 152  | 152 |
|                                      | y             | 14.5 | 16    | 16    | 22   | 22   | 22  |
| Terminal for cond. cross             |               | 1    | 1     | 1     | 2.5  | 2.5  | 2.5 |
| section (mm <sup>2</sup> ) min.-max. |               | -2.5 | -2.5  | -2.5  | -6   | -6   | -6  |