

## Connector

Part no. 728A




- screw terminals
- with cable gland

## Technical specifications

| Ampere                    | 32 A            |
|---------------------------|-----------------|
| Poles                     | 3 p             |
| Voltage                   | 40-50 V         |
| Clock position            | 12 h            |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 227 g           |
| Declaration of Conformity | CN,CQC          |

## Drawing



| Drawing                  | Amp.  |      | 16   |      | 32   |  |
|--------------------------|-------|------|------|------|------|--|
| 3 MB 36                  | Poles | 2    | 3    | 2    | 3    |  |
| Dim. in mm               | а     | 164  | 164  | 164  | 164  |  |
|                          | b     | 55   | 55   | 55   | 55   |  |
|                          | h     | 67   | 67   | 67   | 67   |  |
|                          | m     | 142  | 142  | 142  | 142  |  |
|                          | у     | 24.7 | 24.7 | 24.7 | 24.7 |  |
|                          |       |      |      |      |      |  |
| Terminal for cond. cross |       | 4    | 4    | 4    | 4    |  |
| section (mm²) minmax.    |       | —10  | —10  | —10  | —10  |  |