

## Panel mounted receptacle RAPIDO®

Part no. 995AB




- screwless spring terminals
- suitable for through wiring
- for wall apertures 70 mm Ø
- central fixing

### Technical specifications

|                       |                 |
|-----------------------|-----------------|
| Ampere                | 32 A            |
| Poles                 | 3 p             |
| Voltage               | 230 V           |
| Clock position        | 6 h             |
| Hertz                 | 50-60 Hz        |
| Connection technology | Screw terminals |
| Contact               | standard        |
| Protection type       | IP 44           |
| Weight                | 244 g           |

### Drawing



| Drawing<br>1 MB 468 | Amp.<br>Poles   | 16      |         | 32      |         |         |
|---------------------|---|---------|---------|---------|---------|---------|
|                     |   | 4       | 5       | 3       | 4       | 5       |
| Dim. in mm          | a   | 81      | 81      | 81      | 81      | 81      |
|                     | b   | 66      | 69      | 71      | 71      | 80      |
|                     | c   | 58      | 55      | 66      | 66      | 64      |
|                     | k   | max. 33 | max. 33 | max. 39 | max. 39 | max. 39 |
|                     | h   | 100     | 102     | 101     | 101     | 108     |
|                     | l   | 70      | 70      | 70      | 70      | 70      |
|                     | l1  | 37.75   | 37.75   | 37.75   | 37.75   | 37.75   |
|                     | t   | 2-9     | 2-9     | 2-9     | 2-9     | 2-9     |
|                     | Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. | 1.5     | 1.5     | 2.5     | 2.5     | 2.5     |
|                     |   | -4      | -4      | -10     | -10     | -10     |