

## Panel mounted receptacle

Part no. 1384




- screw terminals
- straight

## Technical specifications

| Ampere                    | 16 A            |
|---------------------------|-----------------|
| Poles                     | 5 p             |
| Voltage                   | 110 V           |
| Clock position            | 4 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Flange                    | 75x75 mm        |
| Fixing hole               | 60x60 mm        |
| Weight                    | 185 g           |
| Declaration of Conformity | CN,CQC          |

## Drawing



| Drawing          | Amp.     | 16  |     |     | 32  |     |     |
|------------------|----------|-----|-----|-----|-----|-----|-----|
| 1 MB 247         | Poles    | 3   | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm       | a        | 75  | 75  | 75  | 75  | 75  | 75  |
|                  | b        | 75  | 75  | 75  | 75  | 75  | 75  |
|                  | c        | 53  | 53  | 55  | 64  | 64  | 65  |
|                  | d        | 60  | 60  | 60  | 60  | 60  | 60  |
|                  | e        | 60  | 60  | 60  | 60  | 60  | 60  |
|                  | f        | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 |
|                  | g.       | 8   | 8   | 8   | 8   | 8   | 8   |
|                  | g.1      | 2   | 2   | 2   | 2   | 2   | 2   |
|                  | h        | 75  | 80  | 83  | 89  | 89  | 100 |
|                  | h1       |     | 6   | 8   | 11  | 11  | 12  |
|                  | k        | 31  | 32  | 32  | 39  | 39  | 39  |
|                  | 1        | 43  | 52  | 54  | 58  | 58  | 62  |
| Terminal for con | d. cross | 1.5 | 1.5 | 1.5 | 2.5 | 2.5 | 2.5 |
| section (mm²) m  | inmax.   | -4  | -4  | -4  | -10 | -10 | -10 |