

## Connector PowerTOP®

Part no. 24559



- screw terminals
- with highly heat resistant contact carrier
- nickel plated contacts
- cable gland and external cable grip

## Technical specifications

|                           |   |
|---------------------------|---|
| Ampere                    | 32 A  |
| Poles                     | 5 p   |
| Voltage                   | 400 V   |
| Clock position            | 6 h   |
| Hertz                     | 50-60 Hz  |
| Connection technology     | Screw terminals   |
| Contact                   | nickel plated contacts, highly heat resistant contact carrier |
| Protection type           | IP 67   |
| Weight                    | 473 g   |
| Declaration of Conformity | DE, VDE, CN, CQC  |

## Drawing



| Drawing<br>3 MB 48/3                 | Amp.<br>Poles | 16   |      |      | 32   |      |      |
|--------------------------------------|---------------|------|------|------|------|------|------|
|                                      |               | 3    | 4    | 5    | 3    | 4    | 5    |
| Dim. in mm                           | a             | 171  | 182  | 194  | 217  | 217  | 229  |
|                                      | b             | 78   | 85   | 96   | 103  | 103  | 110  |
|                                      | h             | 79   | 88   | 95   | 99   | 99   | 105  |
|                                      | y             | 19   | 19   | 22   | 24.5 | 24.5 | 28.5 |
| Terminal for cond. cross             |               | 1    | 1    | 1    | 2.5  | 2.5  | 2.5  |
| section (mm <sup>2</sup> ) min.-max. |               | -2.5 | -2.5 | -2.5 | -6   | -6   | -6   |