

Plug AM-TOP®

Part no. 860




- screw terminals

- single part body cable gland and sealing strain relief and protection against kinking

Technical specifications

| Ampere | 16 A |
|---------------------------|-----------------------|
| Poles | 3 p |
| Voltage | Isolating transformer |
| Clock position | 12 h |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP 44 |
| Weight | 131 g |
| Declaration of Conformity | DE,VDE, CN,CQC |

Drawing



| Drawing | Amp. | 16 | | | 32 | | |
|------------------------------------|-------|-------|-------|-------|-----|-----|------|
| 2 MB 217 | Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | а | 142 | 147 | 147 | 186 | 186 | 180 |
| | b | 53 | 59 | 67 | 70 | 70 | 77 |
| | h | 59 | 69.4 | 76 | 81 | 81 | 89.5 |
| | n | 105.2 | 110.5 | 110.5 | 141 | 141 | 135 |
| | У | 14.5 | 16 | 16 | 22 | 22 | 22 |
| Terminal for cond. cross | | 1 | 1 | 1 | 2.5 | 2.5 | 2.5 |
| section (mm ²) minmax. | | -2.5 | -2.5 | -2.5 | —6 | —6 | —6 |