

Wall mounted receptacle with TwinCONTACT

Part no. 1720



- screwless spring terminals
- suitable for through wiring
- internal fixing
- 4 p and 5 p receptacles the enclosure can be turned 180°

Technical specifications

| | |
|---------------------------|-------------------------|
| Ampere | 16 A |
| Poles | 3 p |
| Voltage | 230 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Connection technology | Screwless - TwinCONTACT |
| Contact | standard |
| Protection type | IP 44 |
| Weight | 117 g |
| Declaration of Conformity | CN,CQC |

Drawing

| Drawing | Amp. | 16 | | |
|------------|---------------------------------------------------------------|---------------------------|-----|-----|
| | | Poles | | |
| 1 MB 209 | | 3 | 4 | 5 |
| Dim. in mm | a | 87 | 100 | 100 |
| | b | 64 | 75 | 75 |
| | c | 99 | 110 | 113 |
| | d | 40 | - | - |
| | d1 | - | 11 | 11 |
| | e | 50 | 59 | 59 |
| | f | 4,5 | 5 | 5 |
| | g- | 4 | 4 | 4 |
| | h | 115 | 125 | 128 |
| | M | 20 | 20 | 20 |
| | M* | M20 (blind) to be cut out | | |
| | Max. cable diam. (mm) | 15 | 15 | 15 |
| | Terminal for cond. cross section (mm ²) min.-max. | 1,5 | 1,5 | 1,5 |
| | | -4 | -4 | -4 |