

## Connector PowerTOP plus

Part no. 3277



- X-CONTACT®
- highly heat resistant contact carrier
- frame terminals
- cable gland and sealing
- strain relief and protection against kinking

## Technical specifications

|                           |   |
|---------------------------|---|
| Ampere                    | 63 A  |
| Poles                     | 4 p   |
| Voltage                   | 500 V   |
| Clock position            | 7 h   |
| Hertz                     | 50-60 Hz  |
| Connection technology     | Screw terminals                                   |
| Contact                   | highly heat resistant contact carrier, X-CONTACT® |
| Protection type           | IP 44   |
| Weight                    | 780 g   |
| Declaration of Conformity | DE, VDE, CN, CQC                                  |

## Drawing

| Drawing<br>3 MB 71                   | Amp.<br>Poles | 63  |     |     |
|--------------------------------------|---------------|-----|-----|-----|
|                                      |               | 3   | 4   | 5   |
| Dim. in mm                           | a             | 268 | 268 | 268 |
|                                      | Øb            | 95  | 95  | 95  |
|                                      | h             | 109 | 109 | 109 |
|                                      | Øy [max]      | 36  | 36  | 36  |
| Terminal for cond. cross             |               | 6   | 6   | 6   |
| section (mm <sup>2</sup> ) min.-max. |               | -16 | -16 | -16 |