

Connector PowerTOP plus

Part no. 3404



- X-CONTACT®
- highly heat resistant contact carrier
- frame terminals
- cable gland and sealing
- strain relief and protection against kinking

Technical specifications

| | |
|---------------------------|---|
| Ampere | 63 A |
| Poles | 4 p |
| Voltage | 110 V |
| Clock position | 4 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | highly heat resistant contact carrier, X-CONTACT® |
| Protection type | IP 67 |
| Weight | 820 g |
| Declaration of Conformity | DE,VDE, CN,CCC |

Drawing

| Drawing 3 MB 70 | Amp. Poles | 63 | | | 125 | | |
|--------------------------------------|---------------|-----|-----|-----|-----|-----|-----|
| | | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 270 | 270 | 270 | 310 | 310 | 310 |
| | Øb | 109 | 109 | 109 | 121 | 121 | 121 |
| | h | 121 | 121 | 121 | 133 | 133 | 133 |
| | Øy [max] | 36 | 36 | 36 | 49 | 49 | 49 |
| Terminal for cond. cross | | 6 | 6 | 6 | 25 | 25 | 25 |
| section (mm ²) min.-max. | | —16 | —16 | —16 | —50 | —50 | —50 |