

## Cepex panel mounted receptacle

Part no. 4273




- screw terminals
- · with labelling field
- suitable for installation in cable ducts and columns

## Technical specifications

| Ampere          | 16 A     |
|-----------------|----------|
| Poles           | 4 p      |
| Voltage         | 400 V    |
| Clock position  | 6 h      |
| Hertz           | 50-60 Hz |
| Protection type | IP 44    |
| Shutter         | false    |
| Weight          | 181 g    |

## Drawing



| Drawing                  | Amp.  |     | 16  |     |     | 32  |     |
|--------------------------|-------|-----|-----|-----|-----|-----|-----|
| 1 MB 318                 | Poles | 3   | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm               | k     | 32  | 32  | 32  | 48  | 48  | 48  |
| Terminal for cond. cross |       | 1.5 | 1.5 | 1.5 | 2.5 | 2.5 | 2.5 |
| section (mm²) minmax.    |       | -4  | -4  | -4  | 6   | -6  | -6  |
|                          |       |     |     |     |     |     |     |
|                          |       |     |     |     |     |     |     |
|                          |       |     |     |     |     |     |     |
|                          |       |     |     |     |     |     |     |
|                          |       |     |     |     |     |     |     |
|                          |       |     |     |     |     |     |     |
|                          |       |     |     |     |     |     |     |
|                          |       |     |     |     |     |     |     |