

Panel mounted inlet

Part no. 473



- screw terminals
- with hinged lid

Technical specifications

| | |
|---------------------------|-----------------|
| Ampere | 32 A |
| Poles | 5 p |
| Voltage | 230 V |
| Clock position | 9 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP 67 |
| Weight | 434 g |
| Declaration of Conformity | DE, VDE |

Drawing



| Drawing | Amp. | 16 | | | | 32 | | 63 | | |
|---------------------------------------------------------------|------|---------|-----|-------|-----|-----|-----|-----|-----|-----|
| | | 2 MB 40 | | Poles | | 3 | 4 | 5 | 4 | 5 |
| Dim. in mm | | | | | | | | | | |
| a | | 85 | 85 | 85 | 85 | 114 | 114 | 114 | 114 | 114 |
| b | | 85 | 85 | 85 | 85 | 114 | 114 | 114 | 114 | 114 |
| c | | 141 | 141 | 141 | 144 | 180 | 180 | 180 | 180 | 180 |
| d | | 70 | 70 | 70 | 70 | 90 | 90 | 90 | 90 | 90 |
| e | | 70 | 70 | 70 | 70 | 90 | 90 | 90 | 90 | 90 |
| f | | 6.2 | 6.2 | 6.2 | 6.2 | 6.2 | 6.2 | 6.2 | 6.2 | 6.2 |
| g | | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 |
| g.1 | | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| h | | 181 | 181 | 181 | 188 | 242 | 242 | 242 | 242 | 242 |
| s | | 86 | 93 | 93 | 100 | 113 | 113 | 113 | 113 | 113 |
| l | | 30 | 30 | 30 | 30 | 40 | 40 | 40 | 40 | 40 |
| Terminal for cond. cross section (mm ²) min.-max. | | 1 | 2.5 | 2.5 | 2.5 | 4 | 4 | 4 | 4 | 4 |
| | | -2.5 | -6 | -6 | -6 | -16 | -16 | -16 | -16 | -16 |