

Cepex grounding-type panel wall receptacle

Part no. 4900



- french-belgian standard
- screw terminals
- one cable entry at top with M 25 stub, one M 25 blind entry (can be cut out) at bottom, one M 20 entry (can be cut out) at the back side, for cables from 7 bis 13 mm Ø
- meeting DIN 18032 standards for ball rebound

Technical specifications

| | |
|-----------------|----------|
| Ampere | 16 A |
| Poles | 3 p+E |
| Voltage | 230 V |
| Hertz | 50-60 Hz |
| Protection type | IP 44 |
| Shutter | true |
| Weight | 260 g |

Drawing

| Drawing 1 MB 312 | Amp. Poles | 16 | | | 32 | | |
|---------------------|---|--------|--------|--------|--------|--------|--------|
| | | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 93 | 93 | 93 | 93 | 93 | 93 |
| | b | 90 | 90 | 90 | 90 | 90 | 90 |
| | c | 87 | 87 | 87 | 99 | 99 | 99 |
| | d | 75 | 75 | 75 | 75 | 75 | 75 |
| | e | 73 | 73 | 73 | 73 | 73 | 73 |
| | f | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 |
| | g | 4.2 | 4.2 | 4.2 | 4.2 | 4.2 | 4.2 |
| | k | 33 | 33 | 33 | 33 | 33 | 33 |
| | y | 25.5 | 25.5 | 25.5 | 25.5 | 25.5 | 25.5 |
| | M | 25x1.5 | 25x1.5 | 25x1.5 | 25x1.5 | 25x1.5 | 25x1.5 |
| | Terminal for cond. cross section (mm ²) min.-max. | 1.5 | 1.5 | 1.5 | 2.5 | 2.5 | 2.5 |
| | | -4 | -4 | -4 | -6 | -6 | -6 |