

## Wall mounted receptacle

Part no. 7248




- screw terminals
- switched
- mechanical DUO-interlock
- RCD (0.03A)
- other leakage current ratings on request
- receptacles can be padlocked

## Technical specifications

Ampere	32 A
Poles	4 p
Voltage	400 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	standard
Protection type	IP 67
Enclosure material	Plastic
Weight	2384 g

## Drawing



Drawing	Amp.	16			32		63			
		Poles		3	4	5	4	5	4	5
1 MB 181/620										
Dim. in mm	a	364	364	364	364	364	460	460		
	b	134	134	134	134	134	180	180		
	c	160	162	163	168	168	202	202		
	d	347	347	347	347	347	440	440		
	e	117	117	117	117	117	160	160		
	f	6.3	6.3	6.3	6.3	6.3	8.1	8.1		
	g	8	8	8	8	8	8	8		
	h	391	395	398	408	411	505	505		
	M	32/40	32/40	32/40	32/40	32/40	40	40		
	M*	2x32	2x32	2x32	2x32	2x32	2x40	2x40		
	Max. cable diam. (mm)	27	27	27	27	27	27	27		
	Terminal for cond. cross section (mm²) min.-max.	1.5	1.5	1.5	2.5	2.5	6	6		
		-4	-4	-4	-10	-10	-25	-25		