

Wall mounted receptacle

Part no. 9377




- screw terminals
- highly resistant to chemicals
- with 2 external fixing points
- receptacles are designed for adding an auxiliary contact switch
- enclosure can be turned 180°

Technical specifications

| | |
|-----------------------|-----------------------|
| Ampere | 32 A |
| Poles | 4 p |
| Voltage | Isolating transformer |
| Clock position | 12 h |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP 67 |
| Weight | 390 g |

Drawing



| Drawing 1 MB 622 | Amp. Poles | 16 | | | 32 | | |
|---------------------|--|----------------------------|------|------|----------------------------|------|------|
| | | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 100 | 100 | 100 | 100 | 100 | 100 |
| | b | 101 | 101 | 101 | 109 | 109 | 109 |
| | c | 117 | 125 | 131 | 157 | 157 | 160 |
| | d | 50 | 50 | 50 | 50 | 50 | 50 |
| | e | 84 | 84 | 84 | 92 | 92 | 92 |
| | f1 | 5.3 | 5.3 | 5.3 | 5.3 | 5.3 | 5.3 |
| | f2 | 5.3 | 5.3 | 5.3 | 5.3 | 5.3 | 5.3 |
| | g | 6.5 | 6.5 | 6.5 | 6.5 | 6.5 | 6.5 |
| | h | 131 | 131 | 132 | 148 | 148 | 148 |
| | i | 24.7 | 24.7 | 24.7 | 27.5 | 27.5 | 27.5 |
| | M | 25 (optional M20) | | | 32 (optional M25) | | |
| | M* | 2x25 (blind) to be cut out | | | 2x25 (blind) to be cut out | | |
| | | 18 (M25) and 15 (M20) | | | 25 (M32) and 18 (M25) | | |
| | Max. cable diam. (mm) | 1.5 | 1.5 | 1.5 | 2.5 | 2.5 | 2.5 |
| | Terminal for cond. cross section (mm²) min.-max. | -4 | -4 | -4 | -6 | -6 | -6 |