

AMAXX® s receptacle combination

Part no. 960009




- pre-wired for installation
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover

Technical specifications

| | |
|---------------------------|---|
| CEE 32 A, 5 p, 400 V | 1 |
| CEE 16 A, 5 p, 400 V | 1 |
| SCHUKO® 16 A, 230 V | 1 |
| Fusing | <ul style="list-style-type: none"> • 1 RCD 40 A, 4 p, 0.03 A • 1 MCB 16 A, 3 p, C • 1 MCB 16 A, 1 p, C |
| Pre-fuse max. | 32 A |
| InA | 32 A |
| RDF | 1 |
| Connection / feeder cable | <ul style="list-style-type: none"> • for 1 cable up to 5 x 10 mm² |
| Protection type | IP 44 |
| Shutter | false |
| Enclosure material | Plastic |
| Weight | 7230 g |
| Height | 650 mm |
| Width | 112.5 mm |

Drawing



Drawing 1 MB 541

Depth dimensions at various fittings.

| Receptacles | Degrees | Depth |
|--------------------|---------|--------|
| SCHUKO® 16A, 230 V | IP 44 | 140 mm |
| | IP 67 | 157 mm |
| CEE 16A, 3p, 230V | IP 44 | 170 mm |
| | IP 67 | 169 mm |
| CEE 16A, 5p, 400V | IP 44 | 172 mm |
| | IP 67 | 174 mm |
| CEE 32A, 5p, 400V | IP 44 | 182 mm |
| | IP 67 | 188 mm |

Cable entries: closed for cut out. 1 x M 25 on top and 1 x M 25 on bottom or 1 x M 32 on top and 1 x M 32 on bottom, additionally: 1 x M 20 on top and bottom to cut out.