

Plug PowerTOP® Xtra

Part no. 13240




- screw terminals
- rubberised grip area
- frame terminals
- highly heat resistant contact carrier
- nickel plated contacts
- cable gland and sealing
- strain relief and protection against kinking
- enclosure with thread lock
- two safety slides

Technical specifications

| Ampere | 63 A |
|---------------------------|---|
| Poles | |
| | 3 p |
| Voltage | 50-250 V |
| Clock position | 3 h |
| Connection technology | Screw terminals |
| Contact | highly heat resistant contact carrier, nickel plated contacts |
| Protection type | IP 67 |
| Weight | 772 g |
| Declaration of Conformity | VDE, EAC |

Drawing



| Drawing | Amp. | | 63 | | | 125 | |
|--------------------------|--------|-----|-----|-----|-------------|-------------|-----|
| 2 MB 225 | Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 250 | 250 | 250 | 290 | 290 | 290 |
| | b | 114 | 114 | 114 | 130 | 130 | 130 |
| | у | 36 | 36 | 36 | 49 | 49 | 49 |
| | | | | | | | |
| Terminal for cond. cross | | 6 | 6 | 6 | 25 | 25 | 25 |
| section (mm²) m | inmax. | —16 | —16 | —16 | — 50 | — 50 | —50 |