

Panel mounted receptacle

Part no. 1365




screw terminals straight

•

Technical specifications

| Ampere | 16 A |
|---------------------------|-----------------|
| Poles | 3 p |
| Voltage | 110 V |
| Clock position | 4 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP 44 |
| Flange | 75x75 mm |
| Fixing hole | 60x60 mm |
| Weight | 137 g |
| Declaration of Conformity | VDE, EAC, CQC |

Drawing



| Drawing | Amp. | 16 | | | 32 | | |
|------------------------------|-----------|-----|-----|-----|-----|-----|-----|
| 1 MB 247 | Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | а | 75 | 75 | 75 | 75 | 75 | 75 |
| | b | 75 | 75 | 75 | 75 | 75 | 75 |
| | c | 53 | 53 | 55 | 64 | 64 | 65 |
| | d | 60 | 60 | 60 | 60 | 60 | 60 |
| | е | 60 | 60 | 60 | 60 | 60 | 60 |
| | f | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 |
| | g. | 8 | 8 | 8 | 8 | 8 | 8 |
| | g.1 | 2 | 2 | 2 | 2 | 2 | 2 |
| | ĥ | 75 | 80 | 83 | 89 | 89 | 100 |
| | h1 | | 6 | 8 | 11 | 11 | 12 |
| | k | 31 | 32 | 32 | 39 | 39 | 39 |
| | 1 | 43 | 52 | 54 | 58 | 58 | 62 |
| Terminal for cor | nd. cross | 1.5 | 1.5 | 1.5 | 2.5 | 2.5 | 2.5 |
| section (mm ²) m | iinmax. | 4 | 4 | -4 | -10 | —10 | -10 |