

## Connector PowerTOP® Xtra

Part no. 14260




- screw terminals
- X-CONTACT®
- with rubberised grip area
- frame terminals
- highly heat resistant contact carrier
- nickel plated contacts
- cable gland and sealing
- strain relief and protection against kinking
- enclosure with thread lock
- two safety slides

### Technical specifications

|                           |   |
|---------------------------|---|
| Ampere                    | 63 A  |
| Poles                     | 5 p   |
| Voltage                   | 400 V   |
| Clock position            | 6 h   |
| Hertz                     | 50-60 Hz  |
| Connection technology     | Screw terminals                                   |
| Contact                   | highly heat resistant contact carrier, X-CONTACT® |
| Protection type           | IP 67   |
| Weight                    | 940 g   |
| Declaration of Conformity | EAC   |

### Drawing



| Drawing<br>3 MB 68                   | Amp.<br>Poles | 63  |     |     | 125 |     |     |
|--------------------------------------|---------------|-----|-----|-----|-----|-----|-----|
|                                      |               | 3   | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm                           | a             | 270 | 270 | 270 | 310 | 310 | 310 |
|                                      | b             | 113 | 113 | 113 | 125 | 125 | 125 |
|                                      | h             | 123 | 123 | 123 | 135 | 135 | 135 |
|                                      | y             | 36  | 36  | 36  | 49  | 49  | 49  |
| Terminal for cond. cross             |               | 6   | 6   | 6   | 25  | 25  | 25  |
| section (mm <sup>2</sup> ) min.-max. |               | -16 | -16 | -16 | -50 | -50 | -50 |