

## Wall mounted receptacle with TwinCONTACT

Part no. 1720



- screwless spring terminals
- suitable for through wiring
- internal fixing
- 4 p and 5 p receptacles the enclosure can be turned 180°

### Technical specifications

|                           |                         |
|---------------------------|-------------------------|
| Ampere                    | 16 A                    |
| Poles                     | 3 p                     |
| Voltage                   | 230 V                   |
| Clock position            | 6 h                     |
| Hertz                     | 50-60 Hz                |
| Connection technology     | Screwless - TwinCONTACT |
| Contact                   | standard                |
| Protection type           | IP 44                   |
| Weight                    | 117 g                   |
| Declaration of Conformity | VDE, EAC, CQC           |

### Drawing

| Drawing<br>1 MB 209 | Amp.<br>Poles   | 16                        |     |     |
|---------------------|---|---------------------------|-----|-----|
|                     |   | 3                         | 4   | 5   |
| Dim. in mm          | a   | 87                        | 100 | 100 |
|                     | b   | 64                        | 75  | 75  |
|                     | c   | 99                        | 110 | 113 |
|                     | d   | 40                        | -   | -   |
|                     | d1  | -                         | 11  | 11  |
|                     | e   | 50                        | 59  | 59  |
|                     | f   | 4,5                       | 5   | 5   |
|                     | g-  | 4                         | 4   | 4   |
|                     | h   | 115                       | 125 | 128 |
|                     | M   | 20                        | 20  | 20  |
|                     | M*  | M20 (blind) to be cut out |     |     |
|                     | Max. cable diam. (mm)   | 15                        | 15  | 15  |
|                     | Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. | 1,5                       | 1,5 | 1,5 |
|                     |   | -4                        | -4  | -4  |