

## Wall mounted receptacle with TwinCONTACT

Part no. 1755



- screwless spring terminals
- suitable for through wiring
- internal fixing
- enclosure base can be turned 180°
- receptacles are designed for adding an auxiliary contact switch

### Technical specifications

|                           |                         |
|---------------------------|-------------------------|
| Ampere                    | 16 A                    |
| Poles                     | 5 p                     |
| Voltage                   | 110 V                   |
| Clock position            | 4 h                     |
| Hertz                     | 50-60 Hz                |
| Connection technology     | Screwless - TwinCONTACT |
| Contact                   | standard                |
| Protection type           | IP 44                   |
| Weight                    | 282 g                   |
| Declaration of Conformity | VDE, EAC, CQC           |

### Drawing



| Drawing<br>1 MB 43 | Amp.<br>Poles   | 16                         |     | 32                         |       |       |
|--------------------|---|----------------------------|-----|----------------------------|-------|-------|
|                    |   | 4                          | 5   | 3                          | 4     | 5     |
| Dim. in mm         | a   | 128                        | 128 | 128                        | 128   | 128   |
|                    | b   | 84                         | 84  | 84                         | 84    | 84    |
|                    | c   | 122                        | 124 | 136                        | 136   | 138   |
|                    | d   | 11                         | 11  | 11                         | 11    | 11    |
|                    | e   | 68                         | 68  | 68                         | 68    | 68    |
|                    | f   | 5.3                        | 5.3 | 5.3                        | 5.3   | 5.3   |
|                    | g   | 4                          | 4   | 4                          | 4     | 4     |
|                    | h   | 144                        | 145 | 158                        | 158   | 160   |
|                    | M   | 25                         | 25  | 32                         | 32    | 32    |
|                    | M*  | 2x25 (blind) to be cut out |     | 2x25 (blind) to be cut out |       |       |
|                    | Max. cable diam. (mm)   | 18                         | 18  | 18/25                      | 18/25 | 18/25 |
|                    | Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. | 1.5                        | 1.5 | 2.5                        | 2.5   | 2.5   |
|                    |   | -4                         | -4  | -10                        | -10   | -10   |