

## Panel mounted receptacle with TwinCONTACT

Part no. 1796



- screwless spring terminals
- suitable for through wiring
- straight

### Technical specifications

|                           |                         |
|---------------------------|-------------------------|
| Ampere                    | 32 A                    |
| Poles                     | 5 p                     |
| Voltage                   | 230 V                   |
| Clock position            | 9 h                     |
| Hertz                     | 50-60 Hz                |
| Connection technology     | Screwless - TwinCONTACT |
| Contact                   | standard                |
| Protection type           | IP 44                   |
| Flange                    | 75x75 mm                |
| Fixing hole               | 60x60 mm                |
| Weight                    | 220 g                   |
| Declaration of Conformity | VDE, EAC, CQC           |

### Drawing



| Drawing<br>1 MB 464 | Amp.<br>Poles   | 16  |     |     | 32  |     |     |
|---------------------|---|-----|-----|-----|-----|-----|-----|
|                     |   | 3   | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm          | a   | 75  | 75  | 75  | 75  | 75  | 75  |
|                     | b   | 75  | 75  | 75  | 75  | 75  | 75  |
|                     | c   | 53  | 53  | 54  | 64  | 64  | 64  |
|                     | d   | 60  | 60  | 60  | 60  | 60  | 60  |
|                     | e   | 60  | 60  | 60  | 60  | 60  | 60  |
|                     | f   | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 |
|                     | g.  | 8   | 8   | 8   | 8   | 8   | 8   |
|                     | g.1   | 2   | 2   | 2   | 2   | 2   | 2   |
|                     | h   | 75  | 80  | 85  | 89  | 89  | 95  |
|                     | h1  |     | 5   | 8   | 10  | 10  | 12  |
|                     | k   | 22  | 22  | 22  | 28  | 28  | 28  |
|                     | l   | 43  | 52  | 57  | 60  | 60  | 64  |
|                     | Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. | 1.5 | 1.5 | 1.5 | 2.5 | 2.5 | 2.5 |
|                     |   | -4  | -4  | -4  | -6  | -6  | -6  |