

**Connector AM-TOP®** 

Part no. 2193



screw terminals


• •

- single part body cable gland and sealing strain relief and protection against kinking

## **Technical specifications**

| Ampere                    | 16 A            |
|---------------------------|-----------------|
| Poles                     | 5 p             |
| Voltage                   | 50-500 V        |
| Clock position            | 10 h            |
| Hertz                     | 100-300 Hz      |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 240 g           |
| Declaration of Conformity | EAC, CQC        |

## Drawing



| Drawing                            | Amp.  | 16   |      |      | 32  |     |     |
|------------------------------------|-------|------|------|------|-----|-----|-----|
| 3 MB 63                            | Poles | 3    | 4    | 5    | 3   | 4   | 5   |
| Dim. in mm                         | а     | 162  | 165  | 167  | 209 | 209 | 208 |
|                                    | b     | 60   | 68   | 76   | 82  | 82  | 89  |
|                                    | h     | 83   | 92   | 98   | 100 | 100 | 108 |
|                                    | у     | 14.5 | 16   | 16   | 22  | 22  | 22  |
|                                    |       |      |      |      |     |     |     |
| Terminal for cond. cross           |       | 1    | 1    | 1    | 2.5 | 2.5 | 2.5 |
| section (mm <sup>2</sup> ) minmax. |       | -2.5 | -2.5 | -2.5 | —6  | —6  | —6  |