

**Plug AM-TOP®**  
Part no. 22289ZC




- screw terminals
- single part body
- highly heat resistant contact carrier
- nickel plated contacts
- cable gland and sealing
- strain relief and protection against kinking

Technical specifications

|                           |   |
|---------------------------|---|
| Ampere                    | 16 A  |
| Poles                     | 4 p   |
| Voltage                   | 400 V   |
| Clock position            | 6 h   |
| Hertz                     | 50-60 Hz  |
| Connection technology     | Screw terminals   |
| Contact                   | nickel plated contacts, highly heat resistant contact carrier |
| Protection type           | IP 44   |
| Weight                    | 153 g   |
| Declaration of Conformity | EAC   |

Drawing



| Drawing<br>2 MB 217                  | Amp.<br>Poles | 16    |       |       | 32  |     |      |
|--------------------------------------|---------------|-------|-------|-------|-----|-----|------|
|                                      |               | 3     | 4     | 5     | 3   | 4   | 5    |
| Dim. in mm                           | a             | 142   | 147   | 147   | 186 | 186 | 180  |
|                                      | b             | 53    | 59    | 67    | 70  | 70  | 77   |
|                                      | h             | 59    | 69.4  | 76    | 81  | 81  | 89.5 |
|                                      | n             | 105.2 | 110.5 | 110.5 | 141 | 141 | 135  |
|                                      | y             | 14.5  | 16    | 16    | 22  | 22  | 22   |
| Terminal for cond. cross             |               | 1     | 1     | 1     | 2.5 | 2.5 | 2.5  |
| section (mm <sup>2</sup> ) min.-max. |               | -2.5  | -2.5  | -2.5  | -6  | -6  | -6   |