

## Plug PowerTOP®

Part no. 3810




- screw terminals
- highly heat resistant contact carrier • •
  - nickel plated contacts
- cable gland and external cable grip

## **Technical specifications**

Ampere	16 A
Poles	4 p
Voltage	500 V
Clock position	7 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	highly heat resistant contact carrier, nickel plated contacts
Protection type	IP 67
Weight	221 g
Declaration of Conformity	VDE, EAC, CQC

## Drawing



	16			32		
Poles	3	4	5	3	4	5
а	162	172	186	199	199	213
b	71	79	89	95	95	102
n	129	139	152	157	157	172
у	19	19	22	24.5	24.5	28.5
nd. cross	1	1	1	2.5	2.5	2.5
iinmax.	-2.5	-2.5	-2.5	—6	—6	—6
	b n	b 71 n 129 y 19 nd. cross 1	b 71 79 n 129 139 y 19 19 nd. cross 1 1	b 71 79 89   n 129 139 152   y 19 19 22   nd. cross 1 1 1	b 71 79 89 95   n 129 139 152 157   y 19 19 22 24.5   nd.cross 1 1 1 2.5	b 71 79 89 95 95   n 129 139 152 157 157   y 19 19 22 24.5 24.5   ad.cross 1 1 1 2.5 25