

Plug PowerTOP®

Part no. 3830




- screw terminals
- highly heat resistant contact carrier
- nickel plated contacts
- cable gland and external cable grip

Technical specifications

| Ampere | 32 A |
|---------------------------|---|
| Poles | 3 p |
| Voltage | 230 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | highly heat resistant contact carrier, nickel plated contacts |
| Protection type | IP 67 |
| Weight | 307 g |
| Declaration of Conformity | VDE, EAC, CQC |

Drawing



| Drawing | Amp. | | 16 | | | 32 | |
|--------------------------|---------|------|--------------|------|------|------------|------|
| 2 MB 171 | Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 162 | 172 | 186 | 199 | 199 | 213 |
| | b | 71 | 79 | 89 | 95 | 95 | 102 |
| | n | 129 | 139 | 152 | 157 | 157 | 172 |
| | у | 19 | 19 | 22 | 24.5 | 24.5 | 28.5 |
| Terminal for cond. cross | | 1 | 1 | 1 | 2.5 | 2.5 | 2.5 |
| section (mm²) m | ninmax. | —2.5 | — 2.5 | —2.5 | 6 | — 6 | -6 |
| | | | | | | | |