

## Plug PowerTOP®

Part no. 3839




- screw terminals
- highly heat resistant contact carrier • •
  - nickel plated contacts
- cable gland and external cable grip

## **Technical specifications**

Ampere	32 A
Poles	4 p
Voltage	110 V
Clock position	4 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	highly heat resistant contact carrier, nickel plated contacts
Protection type	IP 67
Weight	324 g
Declaration of Conformity	VDE, EAC, CQC

## Drawing



Amp.	16			32		
Poles	3	4	5	3	4	5
а	162	172	186	199	199	213
b	71	79	89	95	95	102
n	129	139	152	157	157	172
у	19	19	22	24.5	24.5	28.5
nd. cross	1	1	1	2.5	2.5	2.5
ninmax.	-2.5	-2.5	-2.5	—6	—6	—6
	a b n y nd. cross	a 162 b 71 n 129 y 19 nd. cross 1	a 162 172 b 71 79 n 129 139 y 19 19 nd. cross 1 1	a 162 172 186   b 71 79 89   n 129 139 152   y 19 19 22   id. cross 1 1 1	a 162 172 186 199   b 71 79 89 95   n 129 139 152 157   y 19 19 22 24.5   id. cross 1 1 1 2.5	a 162 172 186 199 199   b 71 79 89 95 95   n 129 139 152 157 157   y 19 19 22 24.5 24.5   id.cross 1 1 1 2.5 2.5