

## **Connector PowerTOP®**

Part no. 3883




- screw terminals
- with highly heat resistant contact carrier
- cable gland and external cable grip

## **Technical specifications**

| Ampere                    | 16 A            |
|---------------------------|-----------------|
| Poles                     | 5 p             |
| Voltage                   | 230 V           |
| Clock position            | 9 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 67           |
| Weight                    | 314 g           |
| Declaration of Conformity | VDE             |

## Drawing



| Drawing                  | Amp.  |      | 16           |      |      | 32   |      |
|--------------------------|-------|------|--------------|------|------|------|------|
| 3 MB 48/3                | Poles | 3    | 4            | 5    | 3    | 4    | 5    |
| Dim. in mm               | а     | 171  | 182          | 194  | 217  | 217  | 229  |
|                          | b     | 78   | 85           | 96   | 103  | 103  | 110  |
|                          | h     | 79   | 88           | 95   | 99   | 99   | 105  |
|                          | у     | 19   | 19           | 22   | 24.5 | 24.5 | 28.5 |
|                          |       |      |              |      |      |      |      |
| Terminal for cond. cross |       | 1    | 1            | 1    | 2.5  | 2.5  | 2.5  |
| section (mm²) minmax.    |       | —2.5 | <b>—</b> 2.5 | —2.5 | 6    | -6   | 6    |