

Connector PowerTOP®

Part no. 3969



- screw terminals
- with highly heat resistant contact carrier
- cable gland and external cable grip

Technical specifications

| | |
|---------------------------|---------------------------------------|
| Ampere | 32 A |
| Poles | 4 p |
| Voltage | 230 V |
| Clock position | 9 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | highly heat resistant contact carrier |
| Protection type | IP 44 |
| Weight | 344 g |
| Declaration of Conformity | EAC |

Drawing



| Drawing 3 MB 51/3 | Amp. Poles | 16 | | | 32 | | |
|--------------------------------------|---------------|------|------|------|------|------|------|
| | | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 165 | 180 | 190 | 214 | 214 | 223 |
| | b | 60 | 68 | 76 | 82 | 82 | 89 |
| | h | 76 | 84 | 90 | 92 | 92 | 99 |
| | y | 19 | 19 | 22 | 24.5 | 24.5 | 28.5 |
| Terminal for cond. cross | | 1 | 1 | 1 | 2.5 | 2.5 | 2.5 |
| section (mm ²) min.-max. | | -2.5 | -2.5 | -2.5 | -6 | -6 | -6 |