

Cepex flush mounted receptacle, alpine white

•

•

Part no. 4243




- screw terminals
- with flush mounted installation box
- meeting DIN 18032 standards for ball rebound

Technical specifications

| Ampere | 16 A |
|---------------------------|----------|
| Poles | 3 p |
| Voltage | 230 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Protection type | IP 44 |
| Shutter | false |
| Weight | 259 g |
| Declaration of Conformity | VDE, EAC |

Drawing



| Drawing | Amp. | 16 | | | 32 | | |
|------------------------------|-----------|-----|-----|-----|-----|-----|-----|
| 1 MB 336 | Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | а | 93 | 93 | 93 | 93 | 93 | 93 |
| | b | 90 | 90 | 90 | 90 | 90 | 90 |
| | c | 95 | 95 | 95 | 95 | 95 | 95 |
| | h | 111 | 111 | 111 | 111 | 111 | 111 |
| | i | 124 | 124 | 124 | 124 | 124 | 124 |
| | k | 33 | 33 | 33 | 33 | 33 | 33 |
| | n | 91 | 91 | 91 | 91 | 91 | 91 |
| | o | 95 | 95 | 95 | 95 | 95 | 95 |
| Terminal for cor | nd. cross | 1.5 | 1.5 | 1.5 | 2.5 | 2.5 | 2.5 |
| section (mm ²) m | ninmax. | —4 | —4 | —4 | 6 | -6 | —6 |