

Connector AM-TOP®

Part no. 516




- screw terminals

- single part body cable gland and sealing strain relief and protection against kinking

Technical specifications

Ampere	16 A
Poles	4 p
Voltage	50-500 V
Clock position	10 h
Hertz	100-300 Hz
Connection technology	Screw terminals
Contact	standard
Protection type	IP 44
Weight	202 g
Declaration of Conformity	VDE, EAC, CQC

Drawing



Amp.		10			32	
Poles	3	4	5	3	4	5
а	162	165	167	209	209	208
b	60	68	76	82	82	89
h	83	92	98	100	100	108
у	14.5	16	16	22	22	22
	1	1	1	2.5	2.5	2.5
nmax.	—2.5	— 2.5	—2.5	-6	—6	— 6
	Poles a b h y	Poles 3 a 162 b 60 h 83 y 14.5	Poles 3 4 a 162 165 b 60 68 h 83 92 y 14.5 16 d. cross 1 1	Poles 3 4 5 a 162 165 167 b 60 68 76 h 83 92 98 y 14.5 16 16 d. cross 1 1 1	Poles 3 4 5 3 a 162 165 167 209 b 60 68 76 82 h 83 92 98 100 y 14.5 16 16 22 d. cross 1 1 1 2.5	Poles 3 4 5 3 4 a 162 165 167 209 209 b 60 68 76 82 82 h 83 92 98 100 100 y 14.5 16 16 22 22 d. cross 1 1 1 2.5 2.5