

Wall mounted receptacle

Part no. 5757



screw terminals


•

- •
- suitable for through wiring with fixing points for terminal strip part no. 40113

## **Technical specifications**

Ampere	16 A
Poles	3 p
Voltage	230 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	standard
Protection type	IP 67
Weight	700 g
Declaration of Conformity	EAC, CQC

## Drawing



Drawing	Amp.		16			32	
1 MB 206	Poles	3	4	5	3	4	5
Dim. in mm	а	225	225	225	225	225	225
	b	118	118	118	118	118	118
	с	144	150	152	155	155	159
	d	208	208	208	208	208	208
	e	101	101	101	101	101	101
	f	6.3	6.3	6.3	6.3	6.3	6.3
	g.	8	8	8	8	8	8
	h	249	251	253	255	253	259
	м	1x25 and 1x32			1x25 and 1x32		
	M*	2x25	2x25	2x25	2x25	2x25	2x25
Max. cable diar	n. (mm)	25	25	25	25	25	25
Terminal for co	nd. cross	1.5	1.5	1.5	2.5	2.5	2.5
section (mm <sup>2</sup> ) n	ninmax.	-4	—4	-4	-10	—10	—10