

Wall mounted receptacle

Part no. 7132




- screw terminals
- with DIN rail, optional fitting of Neozed, Diazed, circuit-breakers and RCD's

Technical specifications

| | |
|---------------------------|-----------------|
| Ampere | 32 A |
| Poles | 5 p |
| Voltage | 400 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP 67 |
| Enclosure material | Plastic |
| Weight | 1115 g |
| Declaration of Conformity | EAC |

Drawing



| Drawing 1 MB 378 | Amp. Poles | 16 | | | 32 | |
|---|---------------|---------------|------|------|---------------|------|
| | | 3 | 4 | 5 | 4 | 5 |
| Dim. in mm | a | 225 | 225 | 225 | 225 | 225 |
| | b | 118 | 118 | 118 | 118 | 118 |
| | c | 144 | 146 | 147 | 152 | 153 |
| | d | 208 | 208 | 208 | 208 | 208 |
| | e | 101 | 101 | 101 | 101 | 101 |
| | f | 6.3 | 6.3 | 6.3 | 6.3 | 6.3 |
| | g | 8 | 8 | 8 | 8 | 8 |
| | h | 252 | 255 | 259 | 268 | 274 |
| | M | 1x25 and 1x32 | | | 1x25 and 1x32 | |
| | M* | 2x25 | 2x25 | 2x25 | 2x25 | 2x25 |
| Max. cable diam. (mm) | | 25 | 25 | 25 | 25 | 25 |
| Terminal for cond. cross section (mm ²) min.-max. | | 1.5 | 1.5 | 1.5 | 2.5 | 2.5 |
| | | -4 | -4 | -4 | -10 | -10 |