

**Power post**  
Part no. 83685



- from steel tube
- wall thickness 4.5 mm
- electro galvanised
- yellow chromated
- powder-coated
- colour: anthracite (RAL 7016)
- hinged supply aperture
- with safety lock
- dimensions (H x Ø): 1050 x 273 mm (inside)
- weight: approx. 60 kg
- aperture at bottom: (H x W) 60 x 70 mm
- fixing flange: Ø 390 mm
- with 4 fixing holes 15.5 mm
- for fixing to an existing fundament

**Technical specifications**

|                           |   |
|---------------------------|---|
| CEE 32 A, 5 p, 400 V      | 1   |
| CEE 16 A, 5 p, 400 V      | 1   |
| SCHUKO® 16 A, 230 V       | 2   |
| Fusing                    | <ul style="list-style-type: none"> <li>• 1 RCD 40 A, 4 p, 0.03 A</li> <li>• 1 MCB 32 A, 3 p, C</li> <li>• 1 MCB 16 A, 3 p, C</li> <li>• 2 MCB's 16 A, 1 p, B</li> </ul> |
| Pre-fuse max.             | 40 A  |
| InA                       | 38 A  |
| RDF                       | 0.6   |
| Connection / feeder cable | <ul style="list-style-type: none"> <li>• for 1 cable up to 5 x 10 mm<sup>2</sup></li> </ul>   |
| Protection type           | IP 44   |
| Shutter                   | false   |
| Enclosure material        | Metal   |
| Weight                    | 60000 g   |
| Height                    | 1050 mm   |
| Diameter                  | 273 mm  |
| Declaration of Conformity | EAC   |

**Drawing**

