

AMAXX® receptacle combination

Part no. 910393

pre-wired for installation

•


enclosure and insert made of AMAPLAST



Technical specifications

| CEE 16 A, 3 p, 110 V | 2 |
|---------------------------|---|
| Connection / feeder cable | for 2 cables up to 3 x 6 mm² |
| Protection type | IP 67 |
| Shutter | false |
| Enclosure material | Plastic |
| Weight | 1420 g |
| Height | 130 mm |
| Width | 225 mm |

Drawing



| Drawing | 1 | MB | 531 |
|---------|---|----|-----|
|---------|---|----|-----|

| P | | B |
|--------------------------------|---------|--------|
| Receptacles | Degrees | Depth |
| SCHUKO [®] 16A, 230 V | IP 44 | 175 mm |
| | IP 67 | 194 mm |
| CEE 16A, 3p, 230V | IP 44 | 204 mm |
| | IP 67 | 205 mm |
| CEE 16A, 5p, 400V | IP 44 | 209 mm |
| | IP 67 | 213 mm |
| CEE 32A, 5p, 400V | IP 44 | 221 mm |
| | IP 67 | 227 mm |
| CEE 63A, 5p, 400V | IP 44 | 248 mm |
| | IP 67 | 248 mm |

Cable entries: closed for cut out. 2 x M 25 each on top and bottom, 2 x M 20 each on top and bottom for cut out.