

## AMAXX® receptacle combination

Part no. 920021




- pre-wired for installation
- hinged to the side
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover

## Technical specifications

|                           |  |
|---------------------------|--|
| CEE 32 A, 5 p, 400 V      | 1  |
| CEE 16 A, 5 p, 400 V      | 1  |
| Fusing                    | <ul style="list-style-type: none"> <li>• 1 MCB 32 A, 3 p, C</li> <li>• 1 MCB 16 A, 3 p, C</li> </ul> |
| Pre-fuse max.             | 63 A   |
| InA                       | 46 A   |
| RDF                       | 0.95   |
| Connection / feeder cable | <ul style="list-style-type: none"> <li>• for 2 cables up to 5 x 10 mm<sup>2</sup></li> </ul>         |
| Protection type           | IP 44  |
| Shutter                   | false  |
| Enclosure material        | Plastic  |
| Weight                    | 3258 g   |
| Height                    | 260 mm   |
| Width                     | 225 mm   |
| Declaration of Conformity | EAC  |

## Drawing



Drawing 1 MB 521

Depth dimensions at various fittings.

| Receptacles        | Degrees | Depth  |
|--------------------|---------|--------|
| SCHUKO® 16A, 230 V | IP 44   | 175 mm |
|                    | IP 67   | 194 mm |
| CEE 16A, 3p, 230V  | IP 44   | 204 mm |
|                    | IP 67   | 205 mm |
| CEE 16A, 5p, 400V  | IP 44   | 209 mm |
|                    | IP 67   | 213 mm |
| CEE 32A, 5p, 400V  | IP 44   | 221 mm |
|                    | IP 67   | 227 mm |
| CEE 63A, 5p, 400V  | IP 44   | 248 mm |
|                    | IP 67   | 248 mm |

Cable entries: closed for cut out. 2 x M 32 each on top and bottom, 2 x M 20 each on top and bottom for cut out.