

## AMAXX® receptacle combination

Part no. 921260




- pre-wired for installation
- hinged to the side
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover

## Technical specifications

|                           |  |
|---------------------------|--|
| French/Belgian standard   | 1  |
| Fitted with               | <ul style="list-style-type: none"> <li>• 1 CEE 16 A, 2 p, 20-25 V</li> </ul>   |
| Fusing                    | <ul style="list-style-type: none"> <li>• 1 RCD 25 A, 2 p, 0.03 A</li> <li>• 1 MCB 6 A, 2 p, C</li> <li>• 1 MCB 16 A, 1 p+N, C</li> <li>• 1 single phase transformer 230 V/ 24 V, 160 VA</li> </ul> |
| Connection / feeder cable | <ul style="list-style-type: none"> <li>• for 1 cable up to 3 x 6 mm<sup>2</sup></li> </ul>   |
| Protection type           | IP 44  |
| Shutter                   | false  |
| Enclosure material        | Plastic  |
| Weight                    | 5690 g   |
| Height                    | 260 mm   |
| Width                     | 225 mm   |

## Drawing



Drawing 1 MB 521

Depth dimensions at various fittings.

| Receptacles        | Degrees | Depth  |
|--------------------|---------|--------|
| SCHUKO® 16A, 230 V | IP 44   | 175 mm |
|                    | IP 67   | 194 mm |
| CEE 16A, 3p, 230V  | IP 44   | 204 mm |
|                    | IP 67   | 205 mm |
| CEE 16A, 5p, 400V  | IP 44   | 209 mm |
|                    | IP 67   | 213 mm |
| CEE 32A, 5p, 400V  | IP 44   | 221 mm |
|                    | IP 67   | 227 mm |
| CEE 63A, 5p, 400V  | IP 44   | 248 mm |
|                    | IP 67   | 248 mm |

Cable entries: closed for cut out. 2 x M 32 each on top and bottom, 2 x M 20 each on top and bottom for cut out.