

## AMAXX® receptacle combination

Part no. 930027



- highly resistant to chemicals
- highly heat resistant contact carrier and nickel plated contacts
- pre-wired for installation
- enclosure front cover grey RAL 7000
- hinged to the side
- fusing behind a transparent cover

## Technical specifications

|                           |   |
|---------------------------|---|
| CEE 16 A, 5 p, 400 V      | 1   |
| SCHUKO® 16 A, 230 V       | 3   |
| Fusing                    | <ul style="list-style-type: none"> <li>• 1 RCD 40 A, 4 p, 0.03 A</li> <li>• 1 MCB 16 A, 3 p, C</li> <li>• 3 MCB's 16 A, 1 p, C</li> </ul> |
| Pre-fuse max.             | 100 A   |
| InA                       | 30 A  |
| RDF                       | 0.95  |
| Connection / feeder cable | <ul style="list-style-type: none"> <li>• for 2 cables up to 5 x 25 mm<sup>2</sup></li> </ul>  |
| Protection type           | IP 67   |
| Shutter                   | false   |
| Enclosure material        | Plastic, high resistance to chemicals   |
| Weight                    | 5580 g  |
| Height                    | 390 mm  |
| Width                     | 225 mm  |
| Declaration of Conformity | EAC   |

## Drawing



Drawing 1 MB 522

Depth dimensions at various fittings.

| Receptacles       | Degrees | Depth  |
|-------------------|---------|--------|
| SCHUKO®16A, 230 V | IP 44   | 175 mm |
|                   | IP 67   | 194 mm |
| CEE 16A, 3p, 230V | IP 44   | 204 mm |
|                   | IP 67   | 205 mm |
| CEE 16A, 5p, 400V | IP 44   | 209 mm |
|                   | IP 67   | 213 mm |
| CEE 32A, 5p, 400V | IP 44   | 221 mm |
|                   | IP 67   | 227 mm |
| CEE 63A, 5p, 400V | IP 44   | 248 mm |
|                   | IP 67   | 248 mm |

Cable entries: closed for cut out. 2 x M 40 each on top and bottom, 2 x M 20 each on top and bottom for cut out.