

## AMAXX® receptacle combination

Part no. 940027




- pre-wired for installation
- hinged to the side
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover
- DUO receptacles switched and interlocked, with highly heat resistant contact carrier and nickel plated contacts

### Technical specifications

|                           |  |
|---------------------------|--|
| CEE 32 A, 4 p, 400 V DUO  | 3  |
| Fusing                    | <ul style="list-style-type: none"> <li>• 3 MCB's 32 A, 3 p, C</li> <li>• 1 earth bolt M 10, V2A</li> </ul> |
| Pre-fuse max.             | 100 A  |
| InA                       | 58 A   |
| RDF                       | 0.6  |
| Connection / feeder cable | <ul style="list-style-type: none"> <li>• for 1 cable up to 5 x 25 mm<sup>2</sup></li> </ul>                |
| Protection type           | IP 67  |
| Shutter                   | false  |
| Enclosure material        | Plastic  |
| Weight                    | 6344 g   |
| Height                    | 520 mm   |
| Width                     | 225 mm   |
| Declaration of Conformity | EAC  |

### Drawing



Drawing 1 MB 523

Depth dimensions at various fittings.

| Receptacles        | Degrees | Depth  |
|--------------------|---------|--------|
| SCHUKO® 16A, 230 V | IP 44   | 186 mm |
|                    | IP 67   | 208 mm |
| CEE 16A, 3p, 230V  | IP 44   | 216 mm |
|                    | IP 67   | 220 mm |
| CEE 16A, 5p, 400V  | IP 44   | 222 mm |
|                    | IP 67   | 226 mm |
| CEE 32A, 5p, 400V  | IP 44   | 231 mm |
|                    | IP 67   | 236 mm |
| CEE 63A, 5p, 400V  | IP 44   | 260 mm |
|                    | IP 67   | 260 mm |

Cable entries: closed for cut out. 2 x M 40 each on top and bottom, 2 x M 20 each on top and bottom for cut out.