

**EverBOX®**

Part no. 9500417



- robust, watertight insulating enclosure, black RAL 9005
- pre-wired for installation
- fusing behind a transparent cover

**Technical specifications**

CEE 125 A, 5 p, 400 V	1	
CEE 63 A, 5 p, 400 V	1	
CEE 32 A, 5 p, 400 V	2	
CEE 16 A, 5 p, 400 V	2	
SCHUKO® 16 A, 230 V	3	
Fusing		<ul style="list-style-type: none"> <li>• 2 RCD's 63 A, 4 p, 0.03 A</li> <li>• 2 MCB's 63 A, 3 p, C</li> <li>• 2 MCB's 32 A, 3 p, C</li> <li>• 2 MCB's 16 A, 3 p, C</li> <li>• 3 MCB's 16 A, 1 p, C</li> </ul>
Pre-fuse max.	125 A	
InA	125 A	
RDF	0.43	
Connection / feeder cable		• 2 m H07RN-F5G25 with CEE-plug 125 A, 5 p, 400 V
Protection type	IP 44	
Shutter	false	
Enclosure material	Plastic	
Weight	28500 g	
Length	560 mm	
Height	340 mm	
Width	350 mm	
Declaration of Conformity	EAC	

**Drawing**

