

**EverBOX®**

Part no. 9500722



- robust, watertight insulating enclosure, black RAL 9005
- pre-wired for installation
- fusing behind a transparent cover

**Technical specifications**

|                           |  |
|---------------------------|--|
| CEE 32 A, 5 p, 400 V      | 1  |
| CEE 16 A, 5 p, 400 V      | 1  |
| SCHUKO® 16 A, 230 V       | 12   |
| Fusing                    | <ul style="list-style-type: none"> <li>• 1 RCD 40 A, 4 p, 0.03 A</li> <li>• 1 MCB 16 A, 3 p, C, 10 kA</li> <li>• 12 MCB's 16 A, 1 p, C, 10 kA</li> <li>• 3 Phase control lights green</li> </ul> |
| Pre-fuse max.             | 32 A   |
| InA                       | 32 A   |
| RDF                       | 1  |
| Connection / feeder cable | <ul style="list-style-type: none"> <li>• 2 m H07RN-F5G6 with CEE-plug 32 A, 5 p, 400 V</li> </ul>  |
| Protection type           | IP 44  |
| Shutter                   | false  |
| Enclosure material        | Plastic  |
| Weight                    | 23876 g  |
| Length                    | 560 mm   |
| Height                    | 340 mm   |
| Width                     | 350 mm   |
| Declaration of Conformity | EAC  |

**Drawing**

